

SIP™ SIMPLEX IDEAL PEERLESS



THE SIMPLEX 5000 ROTARY BLADE SHARPENER uses a milling process, the same process used by the manufacturers, instead of grinding. This results in shelf to shelf times of 2 to 3 minutes per blade. The custom mounting fixture is fully adjustable for any straight edge rotary blade.

Order Number	Description
50001-01	Milling Machine with tooling and power feed
50000-02	Tooling and Fixtures for your mill
50202-01	Digital Read Out
50200-01	Vortec Cooling



THE CUTTING UNIT RACK has an under slung bottom shelf, fully adjustable intermediate shelves and a fixed top shelf that is just over 4 feet high. This allows it to store up to 11 cutting units in a very compact design. The casters are industrial grade and make it easy to roll the rack around in your shop. It is designed to perfectly compliment both the Peerless 7000 Reel Grinder and the Simplex 800 Lift Table. Assembly required. Now UPS shippable.

Order Number 76600-01



THE RHOC REEL HEIGHT OF CUT GAUGE, GROOMER GAUGE AND VERTICUT GAUGE are made from annealed structural tubing that is machined flat to within .002". The tubing prevents any distortion or flexing and the machined surface gives you the same reading at the ends and where the indicator is mounted. This means that you get consistent results, from operator to operator and from gauge to gauge.

Order Number	Description
30005-18	RHOC Reel Height of Cut Gauge
78060-01	Substitute Digital Indicator
30003-18	Groomer Gauge
30002-12	Verticut Gauge



THE SIMPLEX 75 is a bed knife front facer that actually works. Flexible grinding discs in the specially designed housing eliminates gouging, resulting in a uniform, smooth surface.

Order Number 77800-01

SIP
SIMPLEX IDEAL PEERLESS

800-888-6658
sales@sipgrinder.com

2044-03 1/24/2025